

## Material Data Sheet

Film label

### Top material

|                       |                                                   |                  |    |
|-----------------------|---------------------------------------------------|------------------|----|
| Material description: | White, matt polyester film                        |                  |    |
| Printer suitability:  | Colour/monochrome laser printer models and copier |                  |    |
| Thickness             | DIN EN ISO 534                                    | µm               | 58 |
| Grammage              | DIN EN ISO 536                                    | g/m <sup>2</sup> | 80 |

### Adhesive

|                       |                               |
|-----------------------|-------------------------------|
| Material description: | Acrylic, water based adhesive |
|-----------------------|-------------------------------|

### Liner material

|                       |                                         |
|-----------------------|-----------------------------------------|
| Material description: | White kraft paper, one side siliconized |
|-----------------------|-----------------------------------------|

### Laminate

|            |                |                  |     |
|------------|----------------|------------------|-----|
| Thickness: | DIN EN ISO 534 | µm               | 188 |
| Grammage:  | DIN EN ISO 536 | g/m <sup>2</sup> | 204 |

|                      |                |
|----------------------|----------------|
| Service temperature: | -20°C to 80° C |
|----------------------|----------------|

Optimum storage conditions: 23°C at 50% r. h.

Disclaimer: This is an automatically generated data sheet. The given dates are averages values. Information may change. Application tests under field conditions are generally recommended.